

Grand Prix 5000 S TR
HOOKLESS
Safety Information

Hookless – Safety Information for TR tires!

- › **25-622 [development rim 19C]**
 - › Hookless: Max. 5.0 BAR / 73 PSI ($\leq$ 21TSS)
 - › Hooked: Max. 7.5 BAR / 109 PSI ($\leq$ 21C)
- › **28-622 [dev. 19C]**
 - › Hookless: Max. 5.0 BAR / 73 PSI ($\leq$ 25TSS)
 - › Hooked: Max. 6.5 BAR / 94 PSI ($\leq$ 25C)
- › **30/32-622/584 [dev. 21C]**
 - › Max. 5.0 BAR / 73 PSI ($\leq$ 25TSS/C)



INFO:

[ETRTO-2021 for 25-622 on 23TSS
not approved by Conti]

XX-C: Crochet Type Rims (aka Hooked)

XX-TSS: Tubeless Straight-Side Rims (aka Hookless)

Grand Prix 5000 S TR

Tested rim combinations

Manufacturer	Model	Internal	Hooked/Hookless
DT Swiss	ARC MY21	20mm	C
	ERC MY22	22mm	C
ENVE	4.5 ARC	25mm	TSS
	Foundation 45mm	21mm	TSS
HED	Jet 6 / 9	21mm	C
	VANQUISH RC	21mm	C
Mavic	Cosmic Pro Carbon UST MY20	19mm	C
	Cosmic Carbon SLR MY21	19mm	C
	Cosmic SL MY21	21mm	C
Reynolds	AR41	21mm	C
Vision	METRON SL Disc	19mm	C
Zipp	303S	23mm	TSS
	303 Firecrest	25mm	TSS
	858 NSW	19mm	C

Grand Prix 5000 S TR

Mounting – Tips and Tricks



**Air leaking under the tire –
compressor needed?**
► Just add another layer of rim tape!

Tire seems too tight?
► Place both tire beads outside of the
rim to push, rather than pulling it! Use a
tire lever if needed and go with 1cm or
1inch steps forward!

